according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

1-1520 RELAFLOOR 1520 2K EP WV Article No.: Print date: 21.11.2018 Revision date: 24.10.2018 Version: Issue date: 11.10.2018

999998 EN Page 1 / 7



SECTION 1: Identification of the substance/mixture and of the company/undertaking

product identifiers

Article No. (manufacturer/supplier) 1-1520

Identification of the substance or mixture RELAFLOOR 1520 2K EP WV

Grundierung farblos

MV-GEW: 3:1 mit Komponente B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Floor coating

Application in accordance with instructions in associated technical data sheet!

1.3. Details of the supplier of the safety data sheet

manufacturer

FEYCOLOR GmbH

Telephone: 0049 (0)941/60 49 7-0 Maxhuettenstraße 6 Telefax: 0049 (0)941/60 49 7-30 93055 Regensburg E-mail info@fevcolor.com

Website: www.feycolor.com

Dept. responsible for information:

Department for dangerous goods 0049 (0)941/60 49 7-0 E-mail (competent person) sd@feycolor.com

1.4. Emergency telephone number

Emergency telephone number +49 (0) 700 24 11 21 12 (FCM)

Österreichische Vergiftungsinformationszentrale +43 (0) 1406 43 43

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H318 Causes serious eye damage.

Precautionary statements

Wear protective gloves and eye/face protection. P280

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.

Hazard components for labelling

Polyaminoamid-Addukt

Supplemental Hazard information (EU)

not applicable

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / information on ingredients

3.2. **Mixtures**

Product description / chemical characterization

Description Mixture of substances listed below with nonhazardous additions.

Print date:

Version:

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

Article No.: 1-1520 RELAFLOOR 1520 2K EP WV

Revision date: 24.10.2018 999998 EN Issue date: 11.10.2018 Page 2 / 7



Hazardous ingredients

21.11.2018

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification // Remark	

Polyaminoamid-Addukt 25 < 50

Eye Dam. 1 H318

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eve contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No special measures are necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

FEYCOLOR°

Article No.: 1-1520 RELAFLOOR 1520 2K EP WV Print date: 21.11.2018 Revision date: 24.10.2018 Version: 2.0 Issue date: 11.10.2018

999998 EN Page 3 / 7

for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

RELAFLOOR 1520 2K EP WV 1-1520 Article No.: Print date: 21.11.2018 Revision date: 24.10.2018 Version: Issue date: 11.10.2018

999998 EN Page 4 / 7



Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid Colour: refer to label Odour: characteristic **Odour threshold:** not applicable

pH at20 °C: n.a.

Melting point/freezing point: not applicable = 100 °C Initial boiling point and boiling range:

Source: Lösung eines Alkylolammoniumsalzes eines höhermolekularen

sauren Polymeren

Flash point: not applicable not applicable **Evaporation rate:**

Flammability (solid, gas):

Burning time (s): not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: 1,7 Vol-% **Upper explosion limit:** 13,1 Vol-%

Source: 1-methoxy-2-propanol

Vapour pressure at 20 °C: 0,4105 mbar Vapour density: not applicable

Relative density:

Density at20 °C: 1,00 g/cm³

Solubility(ies):

Water solubility (g/L) at20 °C: miscible Partition coefficient: n-octanol/water: see section 12 Auto-ignition temperature: > 200 °C

Source: Lösung eines Alkylolammoniumsalzes eines höhermolekularen

sauren Polymeren

Decomposition temperature: not applicable Viscosity at20 °C: > 160 s 4 mm Method: DIN 53211

Explosive properties: not applicable Oxidising properties: not applicable

9.2. Other information

Solid content (%): 29 Wt %

solvent content:

Organic solvents: 1.00 Wt % 69,10 Wt % Water:

Solvent separation test (%): < 3 Wt % (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

1-1520 RELAFLOOR 1520 2K EP WV Article No.: Print date: 21.11.2018 Revision date: 24.10.2018 Version: Issue date: 11.10.2018

999998 EN Page 5 / 7



Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity, calculated:

Acute toxicity

Based on available data, the classification criteria are not met.

skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

Specific target organ toxicity

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatique, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

12.1. Toxicity

No information available.

Long-term Ecotoxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

Article No.: 1-1520 RELAFLOOR 1520 2K EP WV Print date: 21.11.2018 Revision date: 24.10.2018 Version: 2.0 Issue date: 11.10.2018

FEYCOLOR®

999998 EN Page 6 / 7

Bioconcentration factor (BCF)

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 Waste paint and varnish containing organic solvents or other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code -

Sea transport (IMDG)

EmS-No. not applicable

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Page 7 / 7

Article No.: 1-1520 RELAFLOOR 1520 2K EP WV Print date: 21.11.2018 Revision date: 24.10.2018 Version: 2.0 Issue date: 11.10.2018

VOC-value (in g/L): 20

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/j); VOC limit value: 140 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 15

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

Abbreviations and acronyms

ADR Accord européen relatif au transport international des marchandises dangereuses par route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

AGW (WEL) Occupational Exposure Limit Value

CAS Chemicals Abstract Service

CLP Classification, Labelling and Packaging CMR Carcinogenic, Mutagenic and Reprotoxic

DNEL Derived No-Effect Level

IATA-DGR International Air Transport Association – Dangerous Goods Regulations

ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

IMDG Code International Maritime Code for Dangerous Goods

PBT persistent, bioaccumulative, toxic
PNEC Predicted No Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Règlement concernant le transport international ferroviaire de marchandises Dangereuses

(Regulations concerning the International Carriage of Dangerous Goods by Rail)

UN United Nations LC Lethal Concentration

LD Lethal Dose

VOC Volatile Organic Compounds

vPvB very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.