
Article N Print dat Version:	te: 21.11.20	RELAFLOOR 24 8 Revision date: 24 Issue date: 11.10	1.10.2018	999998 EN Page 1 / 7	N		
SECTION 1: Identification of the substance/mixture and of the company/undertaking							
1.1. p	product identifiers						
	Article No. (manufactu dentification of the su		1-2440 RELAFLOOR 244 Gültig für alle Far MV-GEW: 5:1 mi	btöne			
1.2. R	Relevant identified u	ses of the substance or m	nixture and uses adv	vised against			
FI	Relevant identified u Floor coating Application in accordar	ses: nce with instructions in asso	ciated technical data	sheet!			
1.3. D	Details of the supplie	er of the safety data sheet					
F	nanufacturer EYCOLOR GmbH /laxhuettenstraße 6 /3055 Regensburg		Telephone: 0049 Telefax: 0049 (0) E-mail info@feyc Website: www.fe	941/60 49 7-30 olor.com			
D E	Dept. responsible for Department for danger E-mail (competent per	rous goods son)	0049 (0)941/60 4 sd@feycolor.com				
E	Emergency telephone Emergency telephone Disterreichische Vergif		+49 (0) 700 24 1 +43 (0) 1406 43 4				
SECTIO	ON 2: Hazards ide	ntification					
С Т	Classification accord	substance or mixture ling to Regulation (EC) No ed as hazardous according Respiratory or ski	to regulation (EC) No	0 1272/2008 [CLP]. May cause an allergic skin reaction.			
L		to Regulation (EC) No. 12	72/2008 [CLP]				
п <	lazard pictograms	g					
	Hazard statements H317	May cause an allergic skin	reaction.				
P P P P	Precautionary statementsP261Avoid breathing dust/fume/gas/mist/vapours/spray.P280Wear protective gloves and eye/face protection.P302 + P352IF ON SKIN: Wash with plenty of soap and water.P303 + P361 + P353IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].P308 + P313IF exposed or concerned: Get medical advice/attention.P501Dispose of contents/container to industrial incineration plant.						
	lazard components	Hazardous Resin					
S	Supplemental Hazaro	I information (EU) not applicable					
2.3. O	Other hazards	- F.F					
Т	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.						
SECTIO	SECTION 3: Composition / information on ingredients						

FFVCOLOR®

SECTION 3: Composition / information on ingredients

3.2. Mixtures Product description / chemical characterization



Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No special measures are necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons: strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up



Article No .:	1-2440	RELAFLOOR 2440 2K PU HS		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	2.11	Issue date: 11.10.2018	Page 3 / 7	

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection



Article No.:	1-2440	RELAFLOOR 2440 2K PU HS	
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN
Version:	2.11	Issue date: 11.10.2018	Page 4 / 7

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1.	Information on basic physical and chemical properties		
	Appearance: Physical state: Colour:	Liquid refer to label	
	Odour:	characteristic	
	Odour threshold:	not applicable	
	pH at20 °C:	n.a.	
	Melting point/freezing point:	not applicable	
	Initial boiling point and boiling range:	160 °C Source: Solvent naphtha (petroleum), light arom.	
	Flash point:	not applicable	
	Evaporation rate:	not applicable	
	Flammability (solid, gas): Burning time (s):	not applicable	
	Upper/lower flammability or explosive limits:		
	Lower explosion limit: Upper explosion limit:	0,6 Vol-% 7 Vol-%	
	opper explosion mint.	Source: Solvent naphtha (petroleum), light arom.	
	Vapour pressure at20 °C:	n.a.	
	Vapour density:	not applicable	
	Relative density: Density at20 °C:	1,54 g/cm³	
	Solubility(ies): Water solubility (g/L) at20 °C:	partially soluble	
	Partition coefficient: n-octanol/water:	see section 12	
	Auto-ignition temperature:	200 °C	
		Source: Polysiloxane	
	Decomposition temperature:	not applicable	
	Viscosity at °C:	> 70 dPas	
	Explosive properties:	not applicable	
	Oxidising properties:	not applicable	
9.2.	Other information		
	Solid content (%):	100 Wt %	
	solvent content: Organic solvents: Water:	0,10 Wt % 0,00 Wt %	
	Solvent separation test (%):	< 3 Wt % (ADR/RID)	
050	TION 10: Stability and reactivity		

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability



Version:	2.11	Issue date: 11.10.2018	999998 EN Page 5 / 7	
Article No.: Print date:	1-2440 21.11.2018	RELAFLOOR 2440 2K PU HS Revision date: 24.10.2018	999998 EN	

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials** No information available.

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity, calculated:

Acute toxicity

Based on available data, the classification criteria are not met.

skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

Specific target organ toxicity

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

Long-term Ecotoxicity

Toxicological data are not available.

- 12.2. Persistence and degradability No information available.
- 12.3. Bioaccumulative potential

Article No.:	1-2440	RELAFLOOR 2440 2K PU HS
Print date:	21.11.2018	Revision date: 24.10.2018
Version:	2.11	Issue date: 11.10.2018



999998 EN Page 6 / 7

No information	available.
----------------	------------

Bioconcentration factor (BCF)

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 Waste paint and varnish containing organic solvents or other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation. 14.1. UN number 14.2. UN proper shipping name 14.3. Transport hazard class(es) not applicable

14.4. Packing group

not applicable 14.5. Environmental hazards

Land transport (ADR/RID) Marine pollutant

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code

Sea transport (IMDG)

EmS-No.

not applicable

not applicable

not applicable

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU legislation



Article No.:	1-2440	RELAFLOOR 2440 2K PU HS		and the second second second second second
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	2.11	Issue date: 11.10.2018	Page 7 / 7	

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 2

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds VOC product category: (Cat. A/j) ; VOC limit value: 500 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 1

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Full text of classified	cation in section 3:			
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.		
Abbreviations and	acronyms			
ADR	Accord européen relatif au transport international Agreement concerning the International Carriag	al des marchandises dangereuses par route (European e of Dangerous Goods by Road)		
AGW (WEL)	Occupational Exposure Limit Value			
CAS	Chemicals Abstract Service			
CLP	Classification, Labelling and Packaging			
CMR	Carcinogenic, Mutagenic and Reprotoxic			
DNEL	Derived No-Effect Level			
IATA-DGR	International Air Transport Association – Dange	rous Goods Regulations		
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air			
IMDG Code	International Maritime Code for Dangerous Goo	ds		
PBT	persistent, bioaccumulative, toxic			
PNEC	Predicted No Effect Concentration			
REACH	Registration, Evaluation, Authorisation and Rest	riction of Chemicals		
RID	Règlement concernant le transport interna (Regulations concerning the International Carria	ational ferroviaire de marchandises Dangereuses ge of Dangerous Goods by Rail)		
UN	United Nations			
LC	Lethal Concentration			
LD	Lethal Dose			
VOC	Volatile Organic Compounds			
vPvB	very persistent and very bioaccumulative			

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.