Article I		RELAFLOOR 358			ETCOLOR
Print da Version		18 Revision date: 24. Issue date: 11.10.		999998 EN Page 1 / 7	
SECT	ION 1: Identificatio	on of the substance/mixt	ure and of the co	ompany/undertaking	
1.1.	product identifiers				
	Article No. (manufactu Identification of the su		1-3585 RELAFLOOR 35 gültig für alle Fai MV-GEW: 6:1 m	rbtöne, matt	
1.2. I	Relevant identified u	ses of the substance or mi	xture and uses ad	vised against	
I	Relevant identified uses Floor coating Application in accordance with instructions in associated technical data sheet!				
1.3. I	Details of the supplie	er of the safety data sheet			
l I	manufacturer FEYCOLOR GmbH Maxhuettenstraße 6 93055 Regensburg		Telephone: 0049 Telefax: 0049 (0) E-mail info@feyo Website: www.fe	color.com	
l I	<b>Dept. responsible fo</b> Department for dange E-mail (competent per	rous goods rson)	0049 (0)941/60 4 sd@feycolor.com		
I	Emergency telephon Emergency telephone Österreichische Vergit		+49 (0) 700 24 1 +43 (0) 1406 43		
SECT	ION 2: Hazards ide	ntification			
2.1.	Classification of the	substance or mixture			
(	Classification accore	ling to Regulation (EC) No	1272/2008 [CLP]		
-	The mixture is classified	ed as hazardous according to		o 1272/2008 [CLP].	
	Eye Dam. 1 / H318	Serious eye damag	ge/eye irritation	Causes serious eye d	amage.
	Label elements				
-		to Regulation (EC) No. 1272	2/2008 [CLP]		
•	Hazard pictograms	r			
	Hazard statements H318	Causes serious eye damage	Э.		
l	<b>Precautionary staten</b> P280 P305 + P351 + P338 P310	Wear protective gloves and	ly with water for sev	veral minutes. Remove contac	t lenses, if present and
I	Hazard components	<b>for labelling</b> Polyaminoamid-Addukt			
:	Supplemental Hazar	•			
2.3.	Other hazards				
-	The substances in the	mixture do not meet the PB	T/vPvB criteria acco	ording to REACH, annex XIII.	
SECT	ION 3: Compositio	n / information on ingred	dients		
	Mixtures				

**FEYCOLOR®** 

3.2. Mixtures

## Product description / chemical characterization

**Description** Mixture of substances listed below with nonhazardous additions.



Article No.:	1-3585	RELAFLOOR 3585 2K EP WV		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	2.0	Issue date: 11.10.2018	Page 2 / 7	

#### Hazardous ingredients

EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification // Remark	

Eye Dam. 1 H318

Additional information

Full text of classification: see section 16

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

## In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

## Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

## After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** No special measures are necessary.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

## Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons: strong water jet

## 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

## 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

## 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it



Article No.:	1-3585	RELAFLOOR 3585 2K EP WV		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	2.0	Issue date: 11.10.2018	Page 3 / 7	

for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

## 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

## Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

## Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

## Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

## 7.3. Specific end use(s)

Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## Occupational exposure limit values:

not applicable

## 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

## **Occupational exposure controls**

#### **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

## Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

## Eye protection

Wear closely fitting protective glasses in case of splashes.

RELAFLOOR 3585 2K EP WV 1-3585 Article No.: Print date: 21.11.2018 Revision date: 24.10.2018 999998 EN Version: 2.0 Issue date: 11.10.2018 Page 4 / 7 **Protective clothing** Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers. **Protective measures** After contact clean skin thoroughly with water and soap or use appropriate cleanser. **Environmental exposure controls** Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties Appearance: Physical state: Liquid Colour: refer to label Odour: characteristic **Odour threshold:** not applicable pH at20 °C: n.a. Melting point/freezing point: not applicable = 100 °CInitial boiling point and boiling range: Source: Lösung eines Alkylolammoniumsalzes eines höhermolekularen sauren Polymeren Flash point: not applicable not applicable **Evaporation rate:** Flammability (solid, gas): Burning time (s): not applicable Upper/lower flammability or explosive limits: Lower explosion limit: 1.7 Vol-% Upper explosion limit: 13,1 Vol-% Source: 1-methoxy-2-propanol Vapour pressure at20 °C: 0,2053 mbar Vapour density: not applicable **Relative density:** Density at20 °C: 1,39 g/cm<sup>3</sup> Solubility(ies): Water solubility (g/L) at20 °C: partially soluble Partition coefficient: n-octanol/water: see section 12 Auto-ignition temperature: not applicable **Decomposition temperature:** not applicable Viscosity at20 °C: > 50 s 6 mm Method: DIN 53211 **Explosive properties:** not applicable not applicable **Oxidising properties:** 9.2. Other information Solid content (%): 53 Wt % solvent content: Organic solvents: 0.50 Wt % Water: 46,00 Wt % < 3 Wt % (ADR/RID) Solvent separation test (%):

**FEYCOLOR**<sup>®</sup>

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

#### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.



Article No.:	1-3585	RELAFLOOR 3585 2K EP WV		
Print date: Version:	21.11.2018	Revision date: 24.10.2018 Issue date: 11.10.2018	999998 EN Page 5 / 7	
version.	2.0	15SUE UALE. 11.10.2010	Faye 577	

## 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

## 10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

## 10.5. Incompatible materials

## 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

## **SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

## 11.1. Information on toxicological effects

Acute toxicity, calculated:

## Acute toxicity

Based on available data, the classification criteria are not met.

## skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

## Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

## **SECTION 12: Ecological information**

#### overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

## 12.1. Toxicity

No information available.

## Long-term Ecotoxicity

No information available.

- 12.2. Persistence and degradability No information available.
- 12.3. Bioaccumulative potential No information available. Bioconcentration factor (BCF)

# Safety Data Sheet

acco	rding to rding to R	a Sheet Regulation (E egulation (EU) : 1-3585 21.11.2018	C) No. 1907/2006 (REACH) 2015/830 RELAFLOOR 3585 2K EP WV Revision date: 24.10.2018	FEYCOLOR®
Versic		2.0	Issue date: 11.10.2018	Page 6 / 7
	No informa	ation available.		
12.4.	Mobility in No informa	<b>1 soil</b> ation available.		
12.5.	Results of	f PBT and vPvB a	issessment	
	The substa	ances in the mixtu	re do not meet the PBT/vPvB criteria acc	cording to REACH, annex XIII.
12.6.		erse effects ation available.		
SEC	TION 13: 0	Disposal consid	lerations	
13.1.	Waste trea	atment methods		
		ite disposal / Pro	duct	
		ow to enter into su	urface water or drains. This material and version of the second	d its container must be disposed of in a safe way. Waste gerous waste.
	List of pro 080111		des/waste designations in accordance e paint and varnish containing organic so	
	packaging Recomme	endation		
			s may be recycled. Vessels not properly	
SEC		Fransport inform		
444	•	•	se of this transport regulation.	
14.1.	UN numbe	er	not applicable	
14.2.	UN prope	r shipping name		
14.3.	Transport	hazard class(es)		
	-	ι. ·	not applicable	
14.4.	Packing g	Iroup		
			not applicable	
14.5.		ental hazards		
		sport (ADR/RID)	not applicable	
	Marine pol		not applicable	
14.6.		recautions for us		
	case of an	always in closed, i accident or leaka n safe handling: se	ge.	hat persons transporting the product know what to do in
	Further in	formation		
	Land tran	sport (ADR/RID)		
		riction code	-	
		port (IMDG)		
			not applicable	

EmS-No.

not applicable

Air transport (ICAO-TI / IATA-DGR)

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## EU legislation

Directive 2010/75/EU on industrial emissions VOC-value (in g/L): 14



Article No.:	1-3585	RELAFLOOR 3585 2K EP WV		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	2.0	Issue date: 11.10.2018	Page 7 / 7	

## Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/j) ; VOC limit value: 140 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 12

## **National regulations**

## **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

## Other regulations, restrictions and prohibition regulations

## 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

## **SECTION 16: Other information**

Full text of classification in section 3:

Full lext of cla		
Eye Dam. 1 / H	H318 Serious eye damage/eye irritation Causes serious eye	ye damage.
Abbreviations	s and acronyms	
ADR	Accord européen relatif au transport international des marchandises dar Agreement concerning the International Carriage of Dangerous Goods b	5 I (I

	Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW (WEL)	Occupational Exposure Limit Value
CAS	Chemicals Abstract Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DNEL	Derived No-Effect Level
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous
	Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport international ferroviaire de marchandises Dangereuses
	(Regulations concerning the International Carriage of Dangerous Goods by Rail)
UN	United Nations
LC	Lethal Concentration
LD	Lethal Dose
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

## **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.