

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
Print date: 21.11.2018
Version: 3.0

ALPOTECT Härter 544-5
Revision date: 24.10.2018
Issue date: 11.10.2018

999998 EN
Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 115-544-5
Identification of the substance or mixture ALPOTECT Härter 544-5
Struktur - Härter H3133

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Hardener for 2 component epoxy resins or coatings.
For details on use please see the related technical data sheet!

1.3. Details of the supplier of the safety data sheet

manufacturer

FEYCOLOR GmbH
Maxhuettenstraße 6
93055 Regensburg

Telephone: 0049 (0)941/60 49 7-0
Telefax: 0049 (0)941/60 49 7-30
E-mail info@feycolor.com
Website: www.feycolor.com

Dept. responsible for information:

Department for dangerous goods 0049 (0)941/60 49 7-0
E-mail (competent person) sd@feycolor.com

1.4. Emergency telephone number

Emergency telephone number +49 (0) 700 24 11 21 12 (FCM)
Österreichische Vergiftungsinformationszentrale +43 (0) 1406 43 43

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
STOT RE 2 / H373	Specific target organ toxicity (repeated exposure)	May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof electrical equipment.
P280 Wear protective gloves and eye/face protection.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
 Print date: 21.11.2018
 Version: 3.0

ALPOTECT Härter 544-5
 Revision date: 24.10.2018
 Issue date: 11.10.2018

999998 EN
 Page 2 / 10

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER or doctor/ physician.
 P405 Keep locked up.
 P501 Dispose of contents/container to industrial incineration plant.

Hazard components for labelling

Fettsäuren, C18-ungesättigt, dimere,oligomere Reaktionsprodukte mit Tallöfettsäuren und Triethylentetramin
 reaction product: bisphenol-A-(epichlorhydrin)
 2-methylpropan-1-ol
 n-butyl acetate
 Xylene
 Trien

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description Zusammensetzung aus Kunstharzen und Lösemitteln, unpigmentiert

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification // Remark	Wt %
68082-29-1	Fettsäuren, C18-ungesättigt, dimere,oligomere Reaktionsprodukte mit Tallöfettsäuren und Triethylentetramin Eye Dam. 1 H318	20 < 25
204-658-1 123-86-4	01-2119485493-29 n-butyl acetate	12,5 < 20
607-025-00-1	Flam. Liq. 3 H226 / STOT SE 3 H336	
201-148-0 78-83-1	01-2119484609-23 2-methylpropan-1-ol	12,5 < 20
603-108-00-1	Flam. Liq. 3 H226 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H336	
215-535-7 1330-20-7	01-2119488216-32 Xylene	10 < 12,5
601-022-00-9	Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Aquatic Chronic 3 H412 / Flam. Liq. 3 H226	
203-550-1 108-10-1	01-2119473980-30 4-methylpentan-2-one	10 < 12,5
606-004-00-4	Flam. Liq. 2 H225 / Acute Tox. 4 H332 / Eye Irrit. 2 H319 / STOT SE 3 H335	
203-539-1 107-98-2	01-2119457435-35 1-methoxy-2-propanol	5 < 10
603-064-00-3	Flam. Liq. 3 H226 / STOT SE 3 H336	
215-535-7 1330-20-7	01-2119488216-32 Xylene	1 < 5
601-022-00-9	Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226	

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
Print date: 21.11.2018
Version: 3.0

ALPOTECT Härter 544-5
Revision date: 24.10.2018
Issue date: 11.10.2018

999998 EN
Page 3 / 10

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317	1 < 5
292-588-2	01-2119487919-13	
90640-67-8	Trien	0,1 < 0,3
612-065-00-8	Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No special measures are necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
Print date: 21.11.2018
Version: 3.0

ALPOTECT Härter 544-5
Revision date: 24.10.2018
Issue date: 11.10.2018

999998 EN
Page 4 / 10

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

MEL/OES, TWA: 724 mg/m³; 150 ppm

MEL/OES, STEL: 966 mg/m³; 200 ppm

2-methylpropan-1-ol

INDEX No. 603-108-00-1 / EC No. 201-148-0 / CAS No. 78-83-1

WEL, TWA: 154 mg/m³; 50 ppm

WEL, STEL: 231 mg/m³; 75 ppm

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

4-methylpentan-2-one

INDEX No. 606-004-00-4 / EC No. 203-550-1 / CAS No. 108-10-1

WEL, TWA: 208 mg/m³; 50 ppm

WEL, STEL: 416 mg/m³; 100 ppm

BMGV, TWA: 20 µmol/L

Remark: 4-methylpentan-2-one; urine; end of exposure or end of shift

Amorphes Siliciumdioxid

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
Print date: 21.11.2018
Version: 3.0

ALPOTECT Härter 544-5
Revision date: 24.10.2018
Issue date: 11.10.2018

999998 EN
Page 5 / 10

EC No. 231-545-4 / CAS No. 7631-86-9

WEL, TWA: 2,4 mg/m³

Remark: (Silica, amorphous; respirable fraction)

WEL, TWA: 6 mg/m³

Remark: (Silica, amorphous; inhalable fraction)

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

WEL, TWA: 375 mg/m³; 100 ppm

WEL, STEL: 560 mg/m³; 150 ppm

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state:

Colour:

Liquid

refer to label

Odour:

characteristic

Odour threshold:

not applicable

pH at 20 °C:

n.a.

Melting point/freezing point:

not applicable

Initial boiling point and boiling range:

108 °C

Source: 2-methylpropan-1-ol

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
Print date: 21.11.2018
Version: 3.0

ALPOTECT Härter 544-5
Revision date: 24.10.2018
Issue date: 11.10.2018

999998 EN
Page 6 / 10

Flash point:	14 °C
Evaporation rate:	not applicable
Flammability (solid, gas):	
Burning time (s):	not applicable
Upper/lower flammability or explosive limits:	
Lower explosion limit:	1,54 Vol-%
Upper explosion limit:	13,1 Vol-%
	Source: 1-methoxy-2-propanol
Vapour pressure at20 °C:	7,4778 mbar
Vapour density:	not applicable
Relative density:	
Density at20 °C:	0,94 g/cm³
Solubility(ies):	
Water solubility (g/L) at20 °C:	partially soluble
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	270 °C
	Source: 1-methoxy-2-propanol
Decomposition temperature:	not applicable
Viscosity at20 °C:	> 45 s 4 mm
	Method: DIN 53211
Explosive properties:	not applicable
Oxidising properties:	not applicable
9.2. Other information	
Solid content (%):	39 Wt %
solvent content:	
Organic solvents:	61,07 Wt %
Water:	0,00 Wt %
Solvent separation test (%):	< 3 Wt % (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity, calculated:

ATEmix calculated, dermal: > 5000 mg/kg

ATEmix calculated, inhalative (vapours): > 20 mg/l

Acute toxicity

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
Print date: 21.11.2018
Version: 3.0

ALPOTECT Härter 544-5
Revision date: 24.10.2018
Issue date: 11.10.2018

999998 EN
Page 7 / 10

1-methoxy-2-propanol
oral, LD50, Rat: 4016 mg/kg
dermal, LD50, Rabbit: 10000 mg/kg
inhalative (vapours), LC50, Rat: 6 mg/l (4 h)

n-butyl acetate
oral, LD50, Rat: 14000 mg/kg
inhalative (vapours), LC50, Rat: > 21 mg/l (4 h)

Xylene
oral, LD50, Rat: 8640 mg/kg
dermal, LD50, Rabbit: > 4200 mg/kg
Harmful in contact with skin.
inhalative (vapours), LC50, Rat: 27,6 mg/l (4 h)
Harmful if inhaled.

skin corrosion/irritation; Serious eye damage/eye irritation

Xylene
Skin (4 h)
Causes skin irritation.
eyes
Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

Specific target organ toxicity

1-methoxy-2-propanol
Specific target organ toxicity (single exposure), drowsiness:
May cause drowsiness or dizziness.

n-butyl acetate
Specific target organ toxicity (single exposure), drowsiness:
May cause drowsiness or dizziness.

Xylene
Specific target organ toxicity (single exposure), Irritation:
May cause respiratory irritation.
Specific target organ toxicity (repeated exposure):

Aspiration hazard

Xylene
Aspiration hazard
May be fatal if swallowed and enters airways.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
Print date: 21.11.2018
Version: 3.0

ALPOTECT Härter 544-5
Revision date: 24.10.2018
Issue date: 11.10.2018

999998 EN
Page 8 / 10

There is no information available on the preparation itself .
Do not allow to enter into surface water or drains.

12.1. Toxicity

Xylene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 2,6 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1 mg/l (48 h)

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Bioconcentration factor (BCF)

Xylene

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 25,9

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 Waste paint and varnish containing organic solvents or other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1866

14.2. UN proper shipping name

Land transport (ADR/RID):

Resin solution

Sea transport (IMDG):

RESIN SOLUTION

Air transport (ICAO-TI / IATA-DGR):

Resin solution

14.3. Transport hazard class(es)

3

14.4. Packing group

Land transport (ADR/RID):

III

for packages > 450 litres:

II

Sea transport (IMDG):

III

for packages > 30 litres:

II

Air transport (ICAO-TI / IATA-DGR):

III

for packages > 30 litres:

II

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
Print date: 21.11.2018
Version: 3.0

ALPOTECT Härter 544-5
Revision date: 24.10.2018
Issue date: 11.10.2018

999998 EN
Page 9 / 10

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code E
for packages > 450 litres: D/E
SONDERVORSCHRIFT 640D

Sea transport (IMDG)

EmS-No. F-E, S-E

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 577

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29
201-148-0 78-83-1	2-methylpropan-1-ol	01-2119484609-23
215-535-7 1330-20-7	Xylene	01-2119488216-32
203-550-1 108-10-1	4-methylpentan-2-one	01-2119473980-30
231-545-4 7631-86-9	Amorphes Siliciumdioxid	01-2119379499-16
203-539-1 107-98-2	1-methoxy-2-propanol	01-2119457435-35
215-535-7 1330-20-7	Xylene	01-2119488216-32
292-588-2 90640-67-8	Trien	01-2119487919-13

SECTION 16: Other information

Full text of classification in section 3:

Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

FEYCOLOR®

Article No.: 115-544-5
Print date: 21.11.2018
Version: 3.0

ALPOTECT Härter 544-5
Revision date: 24.10.2018
Issue date: 11.10.2018

999998 EN
Page 10 / 10

Acute Tox. 4 / H332 Eye Irrit. 2 / H319 STOT RE 2 / H373	Acute toxicity (inhalative) Serious eye damage/eye irritation Specific target organ toxicity (repeated exposure)	Harmful if inhaled. Causes serious eye irritation. May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects. Highly flammable liquid and vapour. May cause an allergic skin reaction. Causes severe skin burns and eye damage.
Asp. Tox. 1 / H304 Aquatic Chronic 3 / H412 Flam. Liq. 2 / H225 Skin Sens. 1 / H317 Skin Corr. 1B / H314	Aspiration hazard Hazardous to the aquatic environment Flammable liquids Respiratory or skin sensitisation skin corrosion/irritation	

Abbreviations and acronyms

ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW (WEL)	Occupational Exposure Limit Value
CAS	Chemicals Abstract Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DNEL	Derived No-Effect Level
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)
UN	United Nations
LC	Lethal Concentration
LD	Lethal Dose
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.