accor	aing to Re	gulation (EU) 2	2015/830			FEYCOLOR °
Article Print da		166	RELAFAN 166 Silobeschic 2018 Revision date: 24.10.2018		999998 EN	TERCOLOR
Versio).2018	Page 1 / 7	
SECT	TION 1: Ide	entification of t	he substance/mix	ture and of the co	mpany/undertaking	
1.1.	product ide	entifiers				
		manufacturer/sup n of the substanc		166 RELAFAN 166 Si oder SILOWEISS gültig für alle Fart	·	
1.2.	Relevant id	lentified uses of	the substance or m	nixture and uses adv	vised against	
1.3.	Details of t	he supplier of th	e safety data sheet			
	manufactur FEYCOLOF Maxhuetten 93055 Rege	R GmbH straße 6 ensburg		Telephone: 0049 Telefax: 0049 (0)9 E-mail info@feyco Website: www.fey	941/60 49 7-30 blor.com	
	Department	onsible for inforr for dangerous go petent person)		0049 (0)941/60 4 sd@feycolor.com		
	Emergency	/ telephone num telephone numbe sche Vergiftungsir		+49 (0) 700 24 11 +43 (0) 1406 43 4	. ,	
SECT	ECTION 2: Hazards identification					
2.1.	2.1. Classification of the substance or mixture					
	Classification according to Regulation (EC) No 1272/2008 [CLP]					
	The mixture	e is classified as n	ot hazardous accord	ling to regulation (EC)	No 1272/2008 [CLP].	
2.2.	.2. Label elements					
	Labelling a	ccording to Reg	ulation (EC) No. 12	72/2008 [CLP]		
	Hazard pic	tograms				
	Hazard sta		plicable			
	Precaution	ary statements	plicable			
	Hazard cor	nponents for lab	-			
	Supplemer EUH208	n tal Hazard infor Conta reactio	ins 1,2-benzisothiazo	bl-3(2H)-one; 2-Methy	I-4-Isothiazolin-3-one .	May produce an allergic
	EUH210		data sheet available	e on request.		
2.3.	Other haza	rds				
					ding to REACH, annex	KXIII.
SECT	TION 3: Co	mposition / inf	ormation on ingre	edients		
	Mixtures					
	Product de	scription / chem	ical characterizatio	n		

 Description
 Zubereitung aus Kunststoffdispersion, Additiven und Wasser

Hazardous ingredients

Classification according to Regulation	(EC) No 1272/2008 [CLP]

EC No. REACH No.		
CAS No.	Chemical name	Wt %
INDEX No.	classification // Remark	

Print date: 21.11.2018 Revision date: 24.10.2018 Version: 2.9 Issue date: 11.10.2018			RELAFAN 166 Silobeschichtung Revision date: 24.10.2018 Issue date: 11.10.2018
--	--	--	---

999998 EN Page 2 / 7

FEYCOLOR[®]

not applicable

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

Description of first aid measures 4.1.

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed No special measures are necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

Methods and material for containment and cleaning up 6.3. Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

Reference to other sections 64

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

RELAFAN 166 Silobeschichtung Revision date: 24.10.2018 999998 EN Issue date: 11.10.2018 Page 3 / 7

7.1. Precautions for safe handling

166

2.9

21.11.2018

Article No.:

Print date:

Version:

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls



Article No.:	166	RELAFAN 166 Silobeschichtung		
Print date: Version:	21.11.2018 2.9	Revision date: 24.10.2018 Issue date: 11.10.2018	999998 EN Page 4 / 7	
vereien.	2.0		i ugo i / i	

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1.	.1. Information on basic physical and chemical properties		
	Appearance:		
	Physical state: Colour:	Liquid refer to label	
	Odour:	characteristic	
	Odour threshold:	not applicable	
	pH at20 °C:	n.a.	
	Melting point/freezing point:	not applicable	
	Initial boiling point and boiling range:	100 °C Source: Wasser	
	Flash point:	not applicable	
	Evaporation rate:	not applicable	
	Flammability (solid, gas): Burning time (s):	not applicable	
	Upper/lower flammability or explosive limits:		
	Lower explosion limit: Upper explosion limit:	1 Vol-% not applicable	
	Vapour pressure at20 °C:	0,088 mbar	
	Vapour density:	not applicable	
	Relative density:		
	Density at20 °C:	1,29 g/cm³	
	Solubility(ies):		
	Water solubility (g/L) at20 °C:	partially soluble	
	Partition coefficient: n-octanol/water:	see section 12	
	Auto-ignition temperature:	195 °C Source: 1-(2-Butoxy-1-methylethoxy)propan-2-ol	
	Decomposition temperature:	not applicable	
	Viscosity at20 °C:	30 s 4 mm Method: DIN 53211	
	Explosive properties:	not applicable	
	Oxidising properties:	not applicable	
9.2.	Other information		
	Solid content (%):	49 Wt %	
	solvent content:		
	Organic solvents:	2,20 Wt %	
	Water:	48,44 Wt %	
	Solvent separation test (%):	< 3 Wt % (ADR/RID)	

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials



Article No.:	166	RELAFAN 166 Silobeschichtung		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	2.9	Issue date: 11.10.2018	Page 5 / 7	

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity, calculated:

Acute toxicity

Based on available data, the classification criteria are not met.

skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

Specific target organ toxicity

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

No information available.

Long-term Ecotoxicity

No information available.

- 12.2. **Persistence and degradability** No information available.
- 12.3. **Bioaccumulative potential** No information available.

Bioconcentration factor (BCF)

No information available.

12.4. **Mobility in soil** No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

FEYCOLOR®

Article Print d Versio	ate:	166 21.11.2018 2.9	RELAFAN 166 Silobeschichtung Revision date: 24.10.2018 Issue date: 11.10.2018	999998 EN Page 6 / 7
	No informa	ation available.		
SEC	FION 13: [Disposal consid	erations	
13.1.	Appropria Recomme Do not alle	ow to enter into su		container must be disposed of in a safe way. Waste
	080112 packaging Recomme	waste g endation	les/waste designations in accordance will paint and varnish other than those mention may be recycled. Vessels not properly emp	ed in 08 01 11
SEC		Fransport inform		
	UN numb	er	se of this transport regulation. not applicable	
		r shipping name t hazard class(es)	not applicable	
14.4.	Packing g	Iroup	not applicable	
14.5.		ental hazards sport (ADR/RID) llutant	not applicable not applicable	
14.6.	Special provide the second sec	recautions for us	e r upright and safe containers. Make sure that ge.	persons transporting the product know what to do in
	Further in	formation		
		sport (ADR/RID) triction code	-	
	EmS-No.	port (IMDG)	not applicable	
14.7.	-		A-DGR) g to Annex II of Marpol and the IBC Code	
SEC	TION 15: I	Regulatory infor	mation	
			nental regulations/legislation specific fo	r the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions VOC-value (in g/L): 28

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment



Article No.:	166	RELAFAN 166 Silobeschichtung		
Print date: Version:	21.11.2018 2 9	Revision date: 24.10.2018 Issue date: 11.10.2018	999998 EN Page 7 / 7	
vereien.	2.0		ragerri	

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Abbreviations and acronyms

ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European
	Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW (WEL)	Occupational Exposure Limit Value
CAS	Chemicals Abstract Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DNEL	Derived No-Effect Level
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous
	Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport international ferroviaire de marchandises Dangereuses
	(Regulations concerning the International Carriage of Dangerous Goods by Rail)
UN	United Nations
LC	Lethal Concentration
LD	Lethal Dose
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.