4000			.013/030			<b>FEYCOLOR</b> <sup>®</sup>
Article Print o Versio	date:	178 21.11.2018 1.5	RELAFAN 178 Ro Revision date: 24. Issue date: 12.04.	10.2018	999998 EN Page 1 / 7	FEICOLOK
SEC	TION 1: Id	entification of tl	he substance/mixt	ure and of the comp	any/undertaking	I
1.1.	product id	entifiers				
		(manufacturer/sup on of the substanc		178 RELAFAN 178 Rohb Konzentrat, sehr emi	0	
1.2.	Relevant i	dentified uses of	the substance or mi	xture and uses advise	ed against	
	Floor coatir	5	h instructions in assoc	iated technical data she	et!	
1.3.	Details of	the supplier of th	e safety data sheet			
	manufactu FEYCOLO Maxhuetter 93055 Reg	R GmbH nstraße 6		Telephone: 0049 (0) Telefax: 0049 (0)941 E-mail info@feycolor Website: www.feycol	/60 49 7-30 .com	
	• •	onsible for inforr				
		t for dangerous go npetent person)	oods	0049 (0)941/60 49 7- sd@feycolor.com	-0	
1.4.	Emergency	y telephone num v telephone numbe sche Vergiftungsir		+49 (0) 700 24 11 21 +43 (0) 1406 43 43	12 (FCM)	
SEC	TION 2: Ha	zards identifica	ation			
2.1.	Classificat	tion of the substa	ince or mixture			
	Classificat	tion according to	Regulation (EC) No	1272/2008 [CLP]		
	The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].					

## 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms

#### Hazard statements

not applicable

#### **Precautionary statements**

not applicable Hazard components for labelling

not applicable

Supplemental Hazard information (EU)

not applicable

## 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## **SECTION 3: Composition / information on ingredients**

#### 3.2. Mixtures

Product description / chemical characterization		
Description	Zubereitung aus Kunststoffdispersion, Additiven und Wasser	

## **Hazardous ingredients**

Classification according to Regulation (EC) No 1272/2008 [	CLP]
--	------

Classification a	ccording to Regulation (EC) NO 1272/2006 [CLP]	
EC No.	REACH No.	
CAS No.	Chemical name	
INDEX No.	classification // Remark	

siegler Sector FEYCOLOR®

Article No.: Print date:	178 21.11.2018	RELAFAN 178 Rohbodenversiegler Revision date: 24.10.2018	999998 EN	
Version:	1.5	Issue date: 12.04.2018	Page 2 / 7	

not applicable

#### Additional information

Full text of classification: see section 16

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

## After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

## After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. **Indication of any immediate medical attention and special treatment needed** No special measures are necessary.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

## Extinguishing media which must not be used for safety reasons:

strong water jet

## 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

## 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

## 6.3. **Methods and material for containment and cleaning up** Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

## 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

## **SECTION 7: Handling and storage**



Article No.:	178	RELAFAN 178 Rohbodenversiegler		
Print date: Version:	21.11.2018 1.5	Revision date: 24.10.2018 Issue date: 12.04.2018	999998 EN Page 3 / 7	
version.	1.0	13500 0010. 12.04.2010	i uge o / i	

## 7.1. Precautions for safe handling

## Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

## Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

## Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

## Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

## 7.3. Specific end use(s)

Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## Occupational exposure limit values:

not applicable

## 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

## **Occupational exposure controls**

## **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

## Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

## Eye protection

Wear closely fitting protective glasses in case of splashes.

## **Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

## **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls



Article No.:	178	RELAFAN 178 Rohbodenversiegler		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	1.5	Issue date: 12.04.2018	Page 4 / 7	

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

## **SECTION 9: Physical and chemical properties**

Information on basic physical and chemical properties			
i o label			
cteristic			
oplicable			
oplicable			
<b>:</b> e: Wasser			
oplicable			
oplicable			
oplicable			
ol-% oplicable			
•			
not applicable			
/cm³			
ble			
ection 12			
oplicable			
oplicable			
• <b>mm</b> d: DIN 53211			
oplicable			
oplicable			
%			
Vt % Wt %			
t % (ADR/RID)			

## 10.1. Reactivity

## 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

## 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

## 10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

- 10.5. Incompatible materials
- 10.6. Hazardous decomposition products



Article No.:	178	RELAFAN 178 Rohbodenversiegler		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	1.5	Issue date: 12.04.2018	Page 5 / 7	

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

## **SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

## 11.1. Information on toxicological effects

#### Acute toxicity, calculated:

## Acute toxicity

Based on available data, the classification criteria are not met.

## skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

## **SECTION 12: Ecological information**

#### overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

## 12.1. Toxicity

No information available.

## Long-term Ecotoxicity

No information available.

- 12.2. **Persistence and degradability** No information available.
- 12.3. **Bioaccumulative potential** No information available.

## **Bioconcentration factor (BCF)**

No information available.

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Other adverse effects

No information available.

**FEYCOLOR**<sup>®</sup> 999998 EN Page 6 / 7

SECTION 13: Disposal considerations					
Version:	1.5	Issue date: 12.04.2018			

## 13.1. Waste treatment methods

## Appropriate disposal / Product

178

21.11.2018

## Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

## List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

## packaging

Article No.:

Print date:

## Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

RELAFAN 178 Rohbodenversiegler

Revision date: 24.10.2018

SEC	TION 14: Transport information		
	No dangerous good in sense of this transport regulation.		
14.1.	UN number		
		not applicable	
14.2.	UN proper shipping name		
14.3.	Transport hazard class(es)		
		not applicable	
14.4.	Packing group		
		not applicable	
14.5.	Environmental hazards		
	Land transport (ADR/RID)	not applicable	
	Marine pollutant	not applicable	
14.6.	Special precautions for user		
	Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8		
	Further information		

# Land transport (ADR/RID)

tunnel restriction code

Sea transport (IMDG)

EmS-No.

not applicable

## Air transport (ICAO-TI / IATA-DGR)

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** legislation

## Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 0

## Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/h) ; VOC limit value: 30 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 0

## National regulations

## **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).



Article No.:	178	RELAFAN 178 Rohbodenversiegler		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	1.5	Issue date: 12.04.2018	Page 7 / 7	

#### Other regulations, restrictions and prohibition regulations

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

## **SECTION 16: Other information**

## Full text of classification in section 3:

#### Abbreviations and acronyms

ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW (WEL)	Occupational Exposure Limit Value
CAS	Chemicals Abstract Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DNEL	Derived No-Effect Level
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous
	Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)
UN	United Nations
LC	Lethal Concentration
LD	Lethal Dose
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

## **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.