according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

CHEMUHYD Spezial-Reflektorlack Revision date: 24.10.2018 190-9006-60 Article No.:

Print date: 21.11.2018 999998 EN Issue date: 11.10.2018 Version: Page 1 / 8



SECTION 1: Identification of the substance/mixture and of the company/undertaking

product identifiers

Article No. (manufacturer/supplier) 190-9006-60

Identification of the substance or mixture CHEMUHYD Spezial-Reflektorlack

silber-metallic

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

manufacturer

FEYCOLOR GmbH

Maxhuettenstraße 6 Telephone: 0049 (0)941/60 49 7-0 93055 Regensburg Telefax: 0049 (0)941/60 49 7-30 E-mail info@feycolor.com Website: www.feycolor.com

Dept. responsible for information:

Department for dangerous goods 0049 (0)941/60 49 7-0 E-mail (competent person) sd@feycolor.com

Emergency telephone number

Emergency telephone number +49 (0) 700 24 11 21 12 (FCM)

Österreichische Vergiftungsinformationszentrale +43 (0) 1406 43 43

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Hazard statements

not applicable

Precautionary statements

not applicable

Hazard components for labelling

not applicable

Supplemental Hazard information (EU)

EUH208 Contains p-tert-butylphenyl-1-(2,3-epoxy)propylether. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

23 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / information on ingredients

Mixtures

Product description / chemical characterization

Mixture of substances listed below with nonhazardous additions. Description

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.		
CAS No.	Chemical name	Wt %	
INDEX No.	classification // Remark		
231-072-3	01-2119529243-45		
7429-90-5	aluminium powder (stabilised)	5 < 10	
013-002-00-1	Flam. Sol. 1 H228		

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



5 < 10

Page 2 / 8

CHEMUHYD Spezial-Reflektorlack Revision date: 24.10.2018 190-9006-60 Article No.: Print date: 21.11.2018 Issue date: 11.10.2018

252-104-2 01-2119450011-60

Dipropylene glycol, monomethyl ether, mixture of isomers Substance with a common (EC) occupational exposure limit value.

258-261-3

34590-94-8

Version:

52933-07-0 Phosphoric acid, isotridecyl ester 0.1 < 0.3

Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Repr. 1B H360 / Aquatic Chronic 2

H411

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

No special measures are necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

CHEMUHYD Spezial-Reflektorlack Revision date: 24.10.2018 190-9006-60 Article No.:

Print date: 21.11.2018 999998 EN Issue date: 11.10.2018 Version: Page 3 / 8



Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limit values:

aluminium powder (stabilised)

INDEX No. 013-002-00-1 / EC No. 231-072-3 / CAS No. 7429-90-5

WEL, TWA: 10 mg/m3 Remark: (inhalable fraction) WEL. TWA: 4 ma/m3 Remark: (respirable fraction)

Dipropylene glycol, monomethyl ether, mixture of isomers

EC No. 252-104-2 / CAS No. 34590-94-8

WEL, TWA: 308 mg/m3; 50 ppm

Additional information

TWA: long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

CHEMUHYD Spezial-Reflektorlack Revision date: 24.10.2018 190-9006-60 Article No.:

Print date: 21.11.2018 999998 EN Issue date: 11.10.2018 Version: Page 4 / 8



apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Flash point:

Evaporation rate:

Physical state: Liquid Colour: refer to label Odour: characteristic **Odour threshold:** not applicable

pH at20 °C: n.a.

Melting point/freezing point: not applicable

100 °C Initial boiling point and boiling range:

> Source: Wasser not applicable not applicable

Flammability (solid, gas):

Burning time (s): not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: 1,1 Vol-% **Upper explosion limit:** 14 Vol-%

Source: Dipropylene glycol, monomethyl ether, mixture of isomers

Vapour pressure at 20 °C: 0,0471 mbar Vapour density: not applicable

Relative density:

Density at 20 °C: 1,07 g/cm³

Solubility(ies):

Water solubility (g/L) at20 °C: miscible see section 12 Partition coefficient: n-octanol/water:

270 °C Auto-ignition temperature:

Source: Dipropylene glycol, monomethyl ether, mixture of isomers

Decomposition temperature: not applicable Viscosity at 20 °C: 35 s 4 mm


Method: DIN 53211

Explosive properties: not applicable **Oxidising properties:** not applicable

9.2. Other information

> Solid content (%): 35 Wt %

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Issue date: 11.10.2018 Version:

999998 EN Page 5 / 8



solvent content:

Organic solvents: 6,78 Wt % Water: 58,45 Wt %

Solvent separation test (%): < 3 Wt % (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity, calculated:

ATEmix calculated, dermal: > 5000 mg/kg ATEmix calculated, inhalative (vapours): > 20 mg/l

Acute toxicity

Based on available data, the classification criteria are not met.

skin corrosion/irritation: Serious eve damage/eve irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Phosphoric acid, isotridecyl ester

Reproductive toxicity

May damage fertility or the unborn child.

Specific target organ toxicity

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatique, amyosthenia, drowsiness, in serious cases: unconsciousness, Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

EC No.	Chemical name	Classification according to EC	
CAS No		regulation 1272/2008 (CLP):	

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

190-9006-60 Article No.:

CHEMUHYD Spezial-Reflektorlack Revision date: 24.10.2018 Issue date: 11.10.2018 Print date: 21.11.2018 999998 EN Version: Page 6 / 8

Phosphoric acid, isotridecyl ester

Repr. 1B

258-261-3 52933-07-0

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

12.1. Toxicity

No information available.

Long-term Ecotoxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Bioconcentration factor (BCF)

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.



according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

190-9006-60 Article No.:

CHEMUHYD Spezial-Reflektorlack Revision date: 24.10.2018 Issue date: 11.10.2018 Print date: 21.11.2018 Version:



999998 EN Page 7 / 8

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID) tunnel restriction code

Sea transport (IMDG)

EmS-No. not applicable

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 75

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No.	Chemical name	REACH No.
CAS No.		
231-072-3	aluminium powder (stabilised)	01-2119529243-45
7429-90-5		
252-104-2	Dipropylene glycol, monomethyl ether, mixture of isomers	01-2119450011-60
34590-94-8		

SECTION 16: Other information

Full text of classification in section 3:

Flam. Sol. 1 / H228 flammable solids Flammable solid. Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation. Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

Repr. 1B / H360 Reproductive toxicity

May damage fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes

of exposure cause the hazard).

Aquatic Chronic 2 / H411 Toxic to aquatic life with long lasting effects. Hazardous to the aquatic environment

Abbreviations and acronyms

ADR Accord européen relatif au transport international des marchandises dangereuses par route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

AGW (WEL) Occupational Exposure Limit Value

Chemicals Abstract Service CAS

CLP Classification, Labelling and Packaging **CMR** Carcinogenic, Mutagenic and Reprotoxic

Derived No-Effect Level **DNEL**

IATA-DGR International Air Transport Association – Dangerous Goods Regulations

ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

IMDG Code International Maritime Code for Dangerous Goods

PBT persistent, bioaccumulative, toxic **PNEC** Predicted No Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 190-9006-60 CHEMUHYD Spezial-Reflektorlack Print date: 21.11.2018 Revision date: 24.10.2018 Issue date: 11.10.2018

Règlement concernant le transport international ferroviaire de marchandises Dangereuses

Page 8 / 8

(Regulations concerning the International Carriage of Dangerous Goods by Rail)

UN United Nations
LC Lethal Concentration
LD Lethal Dose

VOC Volatile Organic Compounds

vPvB very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.