	NL	004		••••••••••••••••••••••••••••••••••••••	FEYCOLOF	٢
Article Print d /ersio	late:	391 21.11.2018 3.0	FEYCONIT 391 E Revision date: 24 Issue date: 11.10	.10.2018	999998 EN Page 1 / 8	
SECT	TION 1: Io	dentification of t	he substance/mixt	ure and of the com	pany/undertaking	
1.1.	product i	dentifiers				
		. (manufacturer/sup ion of the substanc		391 FEYCONIT 391 Ein gültig für alle Farbtö seidenmatt, wasser	òne	
.2.		identified uses of identified uses	the substance or m	ixture and uses advis	ed against	
				neral use in industrial a	pplications by spraying, brushing, rolling or dippir	١g
1.3.			e safety data sheet			
	manufact FEYCOLC Maxhuette 93055 Re	DR GmbH enstraße 6		Telephone: 0049 (0 Telefax: 0049 (0)94 E-mail info@feycolo Website: www.feyco	, 1/60 49 7-30 pr.com	
	Departme	ponsible for inforr nt for dangerous go mpetent person)		0049 (0)941/60 49 sd@feycolor.com	7-0	
1.4.	Emergeno	cy telephone num cy telephone numbe hische Vergiftungsir		+49 (0) 700 24 11 2 +43 (0) 1406 43 43	21 12 (FCM)	
SECI	TION 2: H	lazards identifica	ation			
2.1.	Classifica	ation of the substa	ince or mixture			
	Classifica	ation according to	Regulation (EC) No	1272/2008 [CLP]		
	The mixtu	re is classified as h	azardous according t	o regulation (EC) No 1	272/2008 [CLP].	
	Aquatic C	hronic 2 / H411	Hazardous to the a	aquatic environment	Toxic to aquatic life with long lasting effects.	
2.2.	Label ele					
			ulation (EC) No. 127	2/2008 [CLP]		
	Hazard pi	ictograms				
	×					
	Hazard st	tatements				
	H411	Toxic	to aquatic life with lon	g lasting effects.		
		onary statements				
	P501	-		ner to industrial incinera	ation plant.	
	Hazard co	omponents for lab	elling plicable			
	Supplem	ental Hazard infor	-			
2.3.	Other haz	-	-			
	The subst	ances in the mixtur	e do not meet the PB	T/vPvB criteria accord	ing to REACH, annex XIII.	
SECT	TION 3: C	omposition / inf	ormation on ingre	dients		
	Mixtures					
-		description / chem	ical characterization	n		

EEVCOLOD"

Product description / chemical characterization

Zubereitung aus wasserverdünnbarem Bindemittel, Pigmenten, Lösemittel

Hazardous ingredients

Description

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. REACH No.

FEYCOLOR°

cle No.:	391	FEYCONIT 391 Einschichtlack		
t date: sion:	21.11.2018 3.0	Revision date: 24.10.2018 Issue date: 11.10.2018	999998 EN Page 2 / 8	
CAS No. INDEX N		emical name ssification // Remark		Wt %
231-944- 7779-90-	0 trizi	2119485044-40 nc bis(orthophosphate)		1 < 5
030-011- 203-905-	0 01-	iatic Acute 1 H400 / Aquatic Chronic 1 H41 2119475108-36	0	
111-76-2 603-014-	-00-0 Acu	utoxyethanol ite Tox. 4 H332 / Acute Tox. 4 H312 / Aci I9 / Skin Irrit. 2 H315	ute Tox. 4 H302 / Eye	1 < 5 e Irrit. 2
215-222-	-5 01-	2119463881-32		
1314-13-	-2 zino	c oxide		0,1 < 0,3
030-013-	-00-7 Aqu	atic Acute 1 H400 / Aquatic Chronic 1 H41	0	

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed No special measures are necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent

				FEYCOLOR
Article No.: Print date:	391 21.11.2018	FEYCONIT 391 Einschichtlack Revision date: 24.10.2018	999998 EN	
Version:	3.0	Issue date: 11.10.2018	Page 3 / 8	

authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

2-butoxyethanol

INDEX No. 603-014-00-0 / EC No. 203-905-0 / CAS No. 111-76-2 WEL, TWA: 123 mg/m3; 25 ppm

WEL, STEL: 246 mg/m3; 50 ppm

BMGV, TWA: 240 mmol/mol creatinine

Remark: Butoxyacetic acid; urine; end of exposure or end of shift

zinc oxide

INDEX No. 030-013-00-7 / EC No. 215-222-5 / CAS No. 1314-13-2

MEL/OES, TWA: 5 mg/m3 MEL/OES, STEL: 10 mg/m3 Remark: Smoke

Additional information

TWA : long-term occupational exposure limit value STEL : short-term occupational exposure limit value Ceiling : peak limitation



Article No.:	391	FEYCONIT 391 Einschichtlack		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	3.0	Issue date: 11.10.2018	Page 4 / 8	

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance: Physical state:	Liquid
Colour:	refer to label
Odour:	characteristic
Odour threshold:	not applicable
pH at20 °C:	n.a.
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	100 °C Source: Wasser
Flash point:	not applicable
Evaporation rate:	not applicable
Flammability (solid, gas): Burning time (s):	not applicable
Upper/lower flammability or explosive limits: Lower explosion limit: Upper explosion limit:	1,2 Vol-% 12,6 Vol-% Source: 1,2- Propandiol
Vapour pressure at20 °C:	0,0756 mbar
Vapour density:	not applicable
Relative density: Density at20 °C:	1,34 g/cm³
Solubility(ies): Water solubility (g/L) at20 °C:	partially soluble
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	240 °C Source: 2-butoxyethanol
Decomposition temperature:	not applicable



Article Print o Versio	date:	391 21.11.2018 3.0	FEYCONIT 391 Einschichtlack Revision date: 24.10.2018 Issue date: 11.10.2018	999998 EN Page 5 / 8	TERCOLON
	Viscosity	at20 °C:	> 50 s 6 mm Method: DIN 53211		
	Explosive	e properties:	not applicable		
	Oxidising	properties:	not applicable		
9.2.	Other info	ormation			
	Solid con	tent (%):	58 Wt %		
	solvent c Organic Water:	ontent: solvents:	5,93 Wt % 35,31 Wt %		
	Solvent s	eparation test (%)	: < 3 Wt % (ADR/RID)		

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity, calculated:

ATEmix calculated, oral: > 5000 mg/kg ATEmix calculated, dermal: > 5000 mg/kg ATEmix calculated, inhalative (vapours): > 20 mg/l

Acute toxicity

Based on available data, the classification criteria are not met.

skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

Specific target organ toxicity

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye



Article No.:	391	FEYCONIT 391 Einschichtlack	
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN
Version:	3.0	Issue date: 11.10.2018	Page 6 / 8

irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

No information available.

Long-term Ecotoxicity

No information available.

- 12.2. **Persistence and degradability** No information available.
- 12.3. **Bioaccumulative potential** No information available.

Bioconcentration factor (BCF)

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 Waste paint and varnish containing organic solvents or other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

		UN 3082
14.2.	UN proper shipping name	
	Land transport (ADR/RID):	Environmentally hazardous substance, liquid, n.o.s. (Trizinkbis (orthophosphat))
	Sea transport (IMDG):	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Trizinkbis (orthophosphat))
	Air transport (ICAO-TI / IATA-DGR):	Environmentally hazardous substance, liquid, n.o.s. (Trizinkbis (orthophosphat))
14.3.	Transport hazard class(es)	
		9
14.4.	Packing group	
		III
14.5.	Environmental hazards	
	Land transport (ADR/RID)	UMWELTGEFÄHRDEND

Article		391		Einschichtlack		FEICOLON
Print o Versio		21.11.2018 3.0	Revision date: Issue date: 11.		999998 EN Page 7 / 8	
	Marine pollutant			p / Trizinkbis (orthophosphat		
14.6.	-	ecautions for use	er		phosphat)	
	Transport a case of an		pright and safe con	ntainers. Make sure t	hat persons transporting	g the product know what to do in
	Further inf	ormation				
	Land trans	port (ADR/RID)				
	tunnel restr	iction code		-		
	in package	s <= 5 litres		Kein Gut der Klass	e 9	
	Sea transp	oort (IMDG)				
	EmS-No.			F-A, S-F		
		s <= 5 litres		not restricted 2.10.	2.7	
	-	ort (ICAO-TI / IAT	A-DGR)	not restricted not re	a triata d	
147		s <= 5 litres in bulk according	n to Annox II of M	not restricted not re arpol and the IBC C		
14.7.	not applica		g to Annex II of Ma	arpoi and the IBC C	oue	
SEC	• •		motion			
		Regulatory infor				
15.1.	•		nental regulations	/legislation specific	for the substance or	mixture
	EU legislat					
		010/75/EU on inc (in g/L): 83	lustrial emissions	i		
			e limitation of emi	ssions of volatile or	ganic compounds	
			A/i) ; VOC limit val		3	
	Maximum \	/OC content (a/L)	of the product in a	ready to use condition	on: 83	

Maximum VOC content (g/L) of the product in a ready to use condition: 83

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No.	Chemical name	REACH No.
CAS No.		
231-944-3	trizinc bis(orthophosphate)	01-2119485044-40
7779-90-0		
203-905-0	2-butoxyethanol	01-2119475108-36
111-76-2		
215-222-5	zinc oxide	01-2119463881-32
1314-13-2		

SECTION 16: Other information

Acute Tox. 4 / H302 Eye Irrit. 2 / H319

Skin Irrit. 2 / H315

Full text of classification i	n section 3:	
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic effects.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in

Acute toxicity (oral)


skin corrosion/irritation

Serious eye damage/eye irritation

Very toxic to aquatic organisms. Very toxic to aquatic life with long lasting effects. Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. Causes serious eye irritation. Causes skin irritation.

FEYCOLO

Abbreviations and acronyms



vPvB very persistent and very bioaccumulative

Further information

Article No.: Print date:

ADR

CAS

CLP

CMR

DNEL

PBT

RID

UN

LC

LD

VOC

PNEC

Version:

Classification according to Regulation (EC) No 1272/2008 [CLP]

Volatile Organic Compounds

Lethal Dose

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.