# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

FEYCONIT 396 Aqua MICA Paint Revision date: 24.10.2018 396 Article No.:

10.12.2018 Print date: Version: Issue date: 11.10.2018



ΕN Page 1 / 7

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### product identifiers

Article No. (manufacturer/supplier) 396

Identification of the substance or mixture FEYCONIT 396 Agua MICA Paint

> for all colors water-borne

#### Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

manufacturer FEYCOLOR GmbH

Maxhuettenstraße 6 93055 Regensburg

Telephone: 0049 (0)941/60 49 7-0 Telefax: 0049 (0)941/60 49 7-30 E-mail info@feycolor.com Website: www.feycolor.com

Dept. responsible for information:

Department for dangerous goods 0049 (0)941/60 49 7-0 E-mail (competent person) sd@feycolor.com

1.4. Emergency telephone number

Emergency telephone number +49 (0) 700 24 11 21 12 (FCM)

Österreichische Vergiftungsinformationszentrale +43 (0) 1406 43 43

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

#### 2.2 Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

**Hazard pictograms** 

**Hazard statements** 

not applicable

**Precautionary statements** 

not applicable

Hazard components for labelling

not applicable

Supplemental Hazard information (EU)

**EUH210** Safety data sheet available on request.

#### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# **SECTION 3: Composition / information on ingredients**

# **Mixtures**

Product description / chemical characterization

Zubereitung aus wasserverdünnbarem Description

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification // Remark	
203-933-3	01-2119475112-47	
112-07-2	2-butoxyethyl acetate	1 < 5
607-038-00-2	Acute Tox. 4 H302 / Acute Tox. 4 H312 / Acute Tox. 4 H332	

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

FEYCONIT 396 Aqua MICA Paint 396 Article No.:

Revision date: 24.10.2018 Print date: 10.12.2018 Version: 2.6

Page 2 / 7 Issue date: 11.10.2018



#### Additional information

Full text of classification: see section 16

#### **SECTION 4: First aid measures**

# Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After indestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### Indication of any immediate medical attention and special treatment needed 4.3.

No special measures are necessary.

#### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

## Extinguishing media which must not be used for safety reasons:

strong water jet

### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### SECTION 6: Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

# 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

# Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

#### 64 Reference to other sections

Observe protective provisions (see section 7 and 8).

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advices on safe handling

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

FEYCONIT 396 Aqua MICA Paint Revision date: 24.10.2018 396 Article No.:

10.12.2018 Print date: Page 3 / 7 Version: 2.6 Issue date: 11.10.2018



Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet.

# SECTION 8: Exposure controls/personal protection

# Control parameters

#### Occupational exposure limit values:

2-butoxyethyl acetate

INDEX No. 607-038-00-2 / EC No. 203-933-3 / CAS No. 112-07-2

WEL, TWA: 133 mg/m3; 20 ppm WEL, STEL: 332 mg/m3; 50 ppm

Remark: (May be absorbed through the skin.)

#### Additional information

TWA: long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

# Occupational exposure controls

# Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

# Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Wear closely fitting protective glasses in case of splashes.

#### **Protective clothing**

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

FEYCONIT 396 Aqua MICA Paint 396 Article No.:

10.12.2018 Revision date: 24.10.2018 Print date: Version: 2.6 Issue date: 11.10.2018

ΕN



Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Colour: refer to label Odour: characteristic **Odour threshold:** not applicable

pH at 20 °C:: n.a.

Melting point/freezing point: not applicable

100 °C Initial boiling point and boiling range:

Source: Wasser

Flash point: not applicable **Evaporation rate:** not applicable

Flammability (solid, gas):

Burning time (s): not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: 1.45 Vol-% **Upper explosion limit:** 12.6 Vol-%

Source: 1,2- Propandiol

Vapour pressure at 20 °C:: 0,0554 mbar Vapour density: not applicable

Relative density:

Density at 20 °C:: 1,48 g/cm<sup>3</sup>

Solubility(ies):

Water solubility (g/L) at 20 °C:: partially soluble Partition coefficient: n-octanol/water: see section 12

200 °C Auto-ignition temperature:

Source: Polysiloxane

**Decomposition temperature:** not applicable Viscosity at 20 °C:: < 50 s 4 mm Method: DIN 53211

**Explosive properties:** not applicable Oxidising properties: not applicable

9.2. Other information

61 Wt % Solid content (%):

solvent content:

Organic solvents: 3.59 Wt % Water: 35,70 Wt %

Solvent separation test (%): < 3 Wt % (ADR/RID)

# **SECTION 10: Stability and reactivity**

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions



# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

FEYCONIT 396 Aqua MICA Paint 396 Article No.:

Print date: 10.12.2018 Revision date: 24.10.2018 Version: Issue date: 11.10.2018

Page 5 / 7



Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

#### **SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

#### 11.1. Information on toxicological effects

## Acute toxicity, calculated:

ATEmix calculated, oral: > 5000 mg/kg ATEmix calculated, dermal: > 5000 mg/kg ATEmix calculated, inhalative (vapours): > 20 mg/l

#### **Acute toxicity**

2-butoxyethyl acetate oral, LD50, Rat:

## skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

## Specific target organ toxicity

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Practical experience/human evidence

### Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

# **SECTION 12: Ecological information**

## overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

No information available.

#### Long-term Ecotoxicity

No information available.

# 12.2. Persistence and degradability

No information available.

# 12.3. Bioaccumulative potential

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

FEYCONIT 396 Aqua MICA Paint Revision date: 24.10.2018 396 Article No.:

10.12.2018 Print date: Version: 2.6 Issue date: 11.10.2018

Page 6 / 7



No information available.

**Bioconcentration factor (BCF)** 

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Appropriate disposal / Product

#### Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

# **SECTION 14: Transport information**

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable Marine pollutant not applicable

## 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

# **Further information**

# Land transport (ADR/RID)

tunnel restriction code

Sea transport (IMDG)

EmS-No. not applicable

Air transport (ICAO-TI / IATA-DGR)

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** legislation

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

Article No.: 396 FEYCONIT 396 Aqua MICA Paint Print date: 10.12.2018 Feyconit 396 Aqua MICA Paint Revision date: 24.10.2018

Version: 2.6 Revision date: 24.10.2018

Version: 2.6 Issue date: 11.10.2018



EN Page 7 / 7

#### Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 54

#### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/i); VOC limit value: 140 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 54

# **National regulations**

#### **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

#### Other regulations, restrictions and prohibition regulations

# 15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No.	Chemical name	REACH No.
CAS No.		
203-933-3	2-butoxyethyl acetate	01-2119475112-47
112-07-2	•	

#### **SECTION 16: Other information**

#### Full text of classification in section 3:

Acute Tox. 4 / H302 Acute toxicity (oral) Harmful if swallowed.

Acute Tox. 4 / H312 Acute toxicity (dermal) Harmful in contact with skin.

Acute Tox. 4 / H332 Acute toxicity (inhalative) Harmful if inhaled.

#### Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL Occupational Exposure Limit Value

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging CMR Carcinogenic, Mutagenic and Reprotoxic

DNEL Derived No-Effect Level

IATA-DGR International Air Transport Association – Dangerous Goods Regulations

ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

IMDG Code International Maritime Code for Dangerous Goods

PBT persistent, bioaccumulative, toxic
PNEC Predicted No Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

UN United Nations
LC Lethal Concentration
LD Lethal Dose

VOC Volatile Organic Compounds

vPvB very persistent and very bioaccumulative

## **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.