

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**FEYCOLOR®**

Article No.: 397  
Print date: 21.11.2018  
Version: 2.6

FEYCONIT 397 Hydro-Decklack  
Revision date: 24.10.2018  
Issue date: 19.12.2017

999998 EN  
Page 1 / 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. product identifiers**

Article No. (manufacturer/supplier) 397  
Identification of the substance or mixture FEYCONIT 397 Hydro-Decklack  
gültig für alle Farbtöne, SM  
wasserverdünnsbar

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

Single pack paint, based on synthetic resin, for general use in industrial applications by spraying, brushing, rolling or dipping

**1.3. Details of the supplier of the safety data sheet**

**manufacturer**

FEYCOLOR GmbH  
Maxhuettenstraße 6  
93055 Regensburg

Telephone: 0049 (0)941/60 49 7-0  
Telefax: 0049 (0)941/60 49 7-30  
E-mail info@feycolor.com  
Website: www.feycolor.com

**Dept. responsible for information:**

Department for dangerous goods 0049 (0)941/60 49 7-0  
E-mail (competent person) sd@feycolor.com

**1.4. Emergency telephone number**

Emergency telephone number +49 (0) 700 24 11 21 12 (FCM)  
Österreichische Vergiftungsinformationszentrale +43 (0) 1406 43 43

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

**2.2. Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**

**Hazard statements**

not applicable

**Precautionary statements**

not applicable

**Hazard components for labelling**

not applicable

**Supplemental Hazard information (EU)**

EUH208 Contains Cobalt borate neodecanoate complex; 2-butanone oxime. May produce an allergic reaction.  
EUH210 Safety data sheet available on request.

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition / information on ingredients**

**3.2. Mixtures**

**Product description / chemical characterization**

**Description** Zubereitung aus wasserverdünnbarem  
Bindemittel, Pigmenten, Lösemittel

**Hazardous ingredients**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No.	REACH No.	Wt %
CAS No.	Chemical name	

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**FEYCOLOR®**

Article No.: 397  
Print date: 21.11.2018  
Version: 2.6

FEYCONIT 397 Hydro-Decklack  
Revision date: 24.10.2018  
Issue date: 19.12.2017

999998 EN  
Page 2 / 8

INDEX No.	classification // Remark	
203-905-0	01-2119475108-36	
111-76-2	2-butoxyethanol	1 < 5
603-014-00-0	Acute Tox. 4 H332 / Acute Tox. 4 H312 / Acute Tox. 4 H302 / Eye Irrit. 2 H319 / Skin Irrit. 2 H315	
202-496-6	01-2119539477-28	
96-29-7	2-butanone oxime	0,3 < 0,5
616-014-00-0	Carc. 2 H351 / Acute Tox. 4 H312 / Eye Dam. 1 H318 / Skin Sens. 1 H317	
245-018-1	01-2119979088-21	
22464-99-9	2-ethylhexanoic acid, zirconium salt	0,1 < 0,3
	Repr. 2 H361	
270-601-2	Cobalt borate neodecanoate complex	0,1 < 0,3
68457-13-6	Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Repr. 2 H361 / Aquatic Acute 1 H400 / Aquatic Chronic 2 H411	

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

No special measures are necessary.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media:**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Extinguishing media which must not be used for safety reasons:**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**FEYCOLOR®**

Article No.: 397  
Print date: 21.11.2018  
Version: 2.6

FEYCONIT 397 Hydro-Decklack  
Revision date: 24.10.2018  
Issue date: 19.12.2017

999998 EN  
Page 3 / 8

and 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

**6.4. Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Precautions against fire and explosion:**

Vapours are heavier than air. Vapours form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

**7.3. Specific end use(s)**

Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limit values:**

2-butoxyethanol

INDEX No. 603-014-00-0 / EC No. 203-905-0 / CAS No. 111-76-2

WEL, TWA: 123 mg/m<sup>3</sup>; 25 ppm

WEL, STEL: 246 mg/m<sup>3</sup>; 50 ppm

BMGV, TWA: 240 mmol/mol creatinine

Remark: Butoxyacetic acid; urine; end of exposure or end of shift

**Additional information**

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**FEYCOLOR®**

Article No.: 397  
Print date: 21.11.2018  
Version: 2.6

FEYCONIT 397 Hydro-Decklack  
Revision date: 24.10.2018  
Issue date: 19.12.2017

999998 EN  
Page 4 / 8

solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Occupational exposure controls**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye protection**

Wear closely fitting protective glasses in case of splashes.

**Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

**Appearance:**

**Physical state:** Liquid  
**Colour:** refer to label

**Odour:** characteristic

**Odour threshold:** not applicable

**pH at 20 °C:** n.a.

**Melting point/freezing point:** not applicable

**Initial boiling point and boiling range:** 100 °C  
Source: Wasser

**Flash point:** not applicable

**Evaporation rate:** not applicable

**Flammability (solid, gas):**  
**Burning time (s):** not applicable

**Upper/lower flammability or explosive limits:**

**Lower explosion limit:** 1,17 Vol-%  
**Upper explosion limit:** 13,1 Vol-%  
Source: 1-methoxy-2-propanol

**Vapour pressure at 20 °C:** 0,0401 mbar

**Vapour density:** not applicable

**Relative density:**  
**Density at 20 °C:** 1,33 g/cm<sup>3</sup>

**Solubility(ies):**  
**Water solubility (g/L) at 20 °C:** partially soluble

**Partition coefficient: n-octanol/water:** see section 12

**Auto-ignition temperature:** 240 °C  
Source: 2-butoxyethanol

**Decomposition temperature:** not applicable

**Viscosity at 20 °C:** > 40 s 6 mm  
Method: DIN 53211

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**FEYCOLOR®**

Article No.: 397  
Print date: 21.11.2018  
Version: 2.6

FEYCONIT 397 Hydro-Decklack  
Revision date: 24.10.2018  
Issue date: 19.12.2017

999998 EN  
Page 5 / 8

<b>Explosive properties:</b>	<b>not applicable</b>
<b>Oxidising properties:</b>	<b>not applicable</b>
9.2. <b>Other information</b>	
<b>Solid content (%):</b>	<b>55 Wt %</b>
<b>solvent content:</b>	
<b>Organic solvents:</b>	<b>3,74 Wt %</b>
<b>Water:</b>	<b>41,01 Wt %</b>
<b>Solvent separation test (%):</b>	<b>&lt; 3 Wt % (ADR/RID)</b>

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

##### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

##### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

##### 10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

##### 10.5. Incompatible materials

##### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

#### SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

##### 11.1. Information on toxicological effects

###### Acute toxicity, calculated:

ATEmix calculated, oral: > 5000 mg/kg

ATEmix calculated, dermal: > 5000 mg/kg

ATEmix calculated, inhalative (vapours): > 20 mg/l

###### Acute toxicity

Based on available data, the classification criteria are not met.

###### skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

###### Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

###### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

###### Specific target organ toxicity

Based on available data, the classification criteria are not met.

###### Aspiration hazard

Based on available data, the classification criteria are not met.

###### Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

###### Overall Assessment on CMR properties

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**FEYCOLOR®**

Article No.: 397  
Print date: 21.11.2018  
Version: 2.6

FEYCONIT 397 Hydro-Decklack  
Revision date: 24.10.2018  
Issue date: 19.12.2017

999998 EN  
Page 6 / 8

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

**SECTION 12: Ecological information**

**overall evaluation**

Classification according to Regulation (EC) No 1272/2008 [CLP]  
There is no information available on the preparation itself .  
Do not allow to enter into surface water or drains.

**12.1. Toxicity**

No information available.

**Long-term Ecotoxicity**

No information available.

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

No information available.

**Bioconcentration factor (BCF)**

No information available.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080112 waste paint and varnish other than those mentioned in 08 01 11

**packaging**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**No dangerous good in sense of this transport regulation.**

**14.1. UN number**

not applicable

**14.2. UN proper shipping name**

**14.3. Transport hazard class(es)**

not applicable

**14.4. Packing group**

not applicable

**14.5. Environmental hazards**

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**FEYCOLOR®**

Article No.: 397  
Print date: 21.11.2018  
Version: 2.6

FEYCONIT 397 Hydro-Decklack  
Revision date: 24.10.2018  
Issue date: 19.12.2017

999998 EN  
Page 7 / 8

**Further information**

**Land transport (ADR/RID)**

tunnel restriction code -

**Sea transport (IMDG)**

EmS-No. not applicable

**Air transport (ICAO-TI / IATA-DGR)**

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions**

VOC-value (in g/L): 50

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**Other regulations, restrictions and prohibition regulations**

**15.2. Chemical Safety Assessment**

**For the following substances of this preparation a chemical safety assessment has been carried out:**

EC No. CAS No.	Chemical name	REACH No.
203-905-0 111-76-2	2-butoxyethanol	01-2119475108-36
202-496-6 96-29-7	2-butanone oxime	01-2119539477-28
245-018-1 22464-99-9	2-ethylhexanoic acid, zirconium salt	01-2119979088-21

**SECTION 16: Other information**

**Full text of classification in section 3:**

Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging the unborn child.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

**Abbreviations and acronyms**

ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW (WEL)	Occupational Exposure Limit Value
CAS	Chemicals Abstract Service
CLP	Classification, Labelling and Packaging

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**FEYCOLOR®**

Article No.: 397 FEYCONIT 397 Hydro-Decklack  
Print date: 21.11.2018 Revision date: 24.10.2018 999998 EN  
Version: 2.6 Issue date: 19.12.2017 Page 8 / 8

---

CMR	Carcinogenic, Mutagenic and Reprotoxic
DNEL	Derived No-Effect Level
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)
UN	United Nations
LC	Lethal Concentration
LD	Lethal Dose
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.