Article No.: 585 RELAPOX 585 2K EP-Beschichtung Print date: 999998 EN Page 1 / 7 Version: 3.0 Issue date: 11.10.2018 999998 EN Page 1 / 7 SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. product identifiers Article No. (manufacturer/supplier) 585 Identification of the substance or mixture Fel APOX 585 2K EP-Beschichtung gültig für alle Farbtöne Vol-MV: 4,2:0,8 mit Härter 585 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: 1.3. Details of the supplier of the safety data sheet manufacturer FEYCOLOR GmbH	
 1.1. product identifiers Article No. (manufacturer/supplier) Identification of the substance or mixture RELAPOX 585 2K EP-Beschichtung gültig für alle Farbtöne Vol-MV: 4,2:0,8 mit Härter 585 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: 1.3. Details of the supplier of the safety data sheet manufacturer 	
Article No. (manufacturer/supplier) 585 Identification of the substance or mixture RELAPOX 585 2K EP-Beschichtung gültig für alle Farbtöne Vol-MV: 4,2:0,8 mit Härter 585 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: 1.3. Details of the supplier of the safety data sheet manufacturer	
Identification of the substance or mixture RELAPOX 585 2K EP-Beschichtung gültig für alle Farbtöne Vol-MV: 4,2:0,8 mit Härter 585 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: 1.3. Details of the supplier of the safety data sheet manufacturer	
Relevant identified uses: 1.3. Details of the supplier of the safety data sheet manufacturer	
manufacturer	
Maxhuettenstraße 6Telephone: 0049 (0)941/60 49 7-093055 RegensburgTelefax: 0049 (0)941/60 49 7-30E-mail info@feycolor.comWebsite: www.feycolor.com	
Dept. responsible for information:Department for dangerous goods0049 (0)941/60 49 7-0E-mail (competent person)sd@feycolor.com	
I.4.Emergency telephone numberEmergency telephone number+49 (0) 700 24 11 21 12 (FCM)Österreichische Vergiftungsinformationszentrale+43 (0) 1406 43 43	
SECTION 2: Hazards identification	
2.1. Classification of the substance or mixture	
Classification according to Regulation (EC) No 1272/2008 [CLP]	
The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].	
Eye Dam. 1 / H318Serious eye damage/eye irritationCauses serious eye damage.	
.2. Label elements	
Labelling according to Regulation (EC) No. 1272/2008 [CLP]	
Hazard pictograms	
Hazard statementsH318Causes serious eye damage.	
Precautionary statementsP280Wear protective gloves and eye/face protection.P305 + P351 + P338IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if p easy to do. Continue rinsing.P310Immediately call a POISON CENTER or doctor/ physician.	present and
Hazard components for labelling Polyaminoamid-Addukt	
Supplemental Hazard information (EU) not applicable	
2.3. Other hazards	
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.	
SECTION 3: Composition / information on ingredients	

3.2. Mixtures

Product description / chemical characterization			
Description	Zubereitung aus Bindemittel, Pigment, Füllstoff, Additiven und Wasser		



Article No.:	585	RELAPOX 585 2K EP-Beschichtung		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	3.0	Issue date: 11.10.2018	Page 2 / 7	

Hazardous ingredients

EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification // Remark	

Eye Dam. 1 H318

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed No special measures are necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons: strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing

Article No.:	585	RELAPOX 585 2K EP-Beschichtung	
Print date:	21.11.2018	Revision date: 24.10.2018	99999
Version:	3.0	Issue date: 11.10.2018	Page
version.	5.0	13500 Udie. 11.10.2010	

999998 EN Page 3 / 7 **FEYCOLOR**[®]

agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage 7.1. Precautions for safe handling

Advises on cofe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing



Article No.: Print date: Version:	585 21.11.2018 3.0	RELAPOX 585 2K EP-Beschichtung Revision date: 24.10.2018 Issue date: 11.10.2018	999998 EN Page 4 / 7	TETEOLON

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Appearance: Physical state:	Liquid
	Colour:	refer to label
	Odour:	characteristic
	Odour threshold:	not applicable
	pH at20 °C:	n.a.
	Melting point/freezing point:	not applicable
	Initial boiling point and boiling range:	= 100 °C
		Source: Lösung eines Alkylolammoniumsalzes eines höhermolekularen sauren Polymeren
	Flash point:	not applicable
	Evaporation rate:	not applicable
	Flammability (solid, gas): Burning time (s):	not applicable
	Upper/lower flammability or explosive limits:	
	Lower explosion limit:	not applicable
	Upper explosion limit:	not applicable
	Vapour pressure at20 °C:	0,1101 mbar
	Vapour density:	not applicable
	Relative density: Density at20 °C:	1,39 g/cm³
	Solubility(ies):	
	Water solubility (g/L) at20 °C:	partially soluble
	Partition coefficient: n-octanol/water:	see section 12
	Auto-ignition temperature:	not applicable
	Decomposition temperature:	not applicable
	Viscosity at20 °C:	> 17 s 4 mm Method: DIN 53211
	Explosive properties:	not applicable
	Oxidising properties:	not applicable
2.	Other information	
	Solid content (%):	50 Wt %
	solvent content:	
	Organic solvents: Water:	0,00 Wt % 49,74 Wt %
	water: Solvent separation test (%):	49,74 Wt % < 3 Wt % (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

9.2

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions



Article No.:	585	RELAPOX 585 2K EP-Beschichtung		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	3.0	Issue date: 11.10.2018	Page 5 / 7	

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity, calculated:

Acute toxicity

Based on available data, the classification criteria are not met.

skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

Specific target organ toxicity

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

Long-term Ecotoxicity

Toxicological data are not available.

- 12.2. **Persistence and degradability** No information available.
- 12.3. **Bioaccumulative potential** No information available.

Bioconcentration factor (BCF)

No information available.

FEYCOLOR°

Version: 12.4. Mobility	3.0	Issue date: 11.10.2018	Page 6 / 7	
Article No.: Print date:	585 21.11.2018	RELAPOX 585 2K EP-Beschichtung Revision date: 24.10.2018	999998 EN	

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 Waste paint and varnish containing organic solvents or other dangerous substances

not applicable

not applicable

not applicable

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

- 14.1. UN number
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- 14.5. Environmental hazards

Land transport (ADR/RID)	not applicable
Marine pollutant	not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code

Sea transport (IMDG) EmS-No.

not applicable

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 6

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds



Article No.:	585	RELAPOX 585 2K EP-Beschichtung		
Print date:	21.11.2018	Revision date: 24.10.2018	999998 EN	
Version:	3.0	Issue date: 11.10.2018	Page 7 / 7	

VOC product category: (Cat. A/j) ; VOC limit value: 140 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 1

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage. Abbreviations and acronyms ADR Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road) AGW (WEL) Occupational Exposure Limit Value **Chemicals Abstract Service** CAS CLP Classification, Labelling and Packaging CMR Carcinogenic, Mutagenic and Reprotoxic DNEL Derived No-Effect Level IATA-DGR International Air Transport Association – Dangerous Goods Regulations ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air International Maritime Code for Dangerous Goods IMDG Code PBT persistent, bioaccumulative, toxic PNEC Predicted No Effect Concentration Registration, Evaluation, Authorisation and Restriction of Chemicals REACH Règlement concernant le transport international ferroviaire de marchandises Dangereuses RID (Regulations concerning the International Carriage of Dangerous Goods by Rail) UN United Nations LC Lethal Concentration LD Lethal Dose VOC Volatile Organic Compounds very persistent and very bioaccumulative vPvB

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.