
					FEYCOLOR®	
Article	e No.: 90-720 Polyesterharz date: 21.11.2018 Revision date: 24.		10 2019	999998 EN		
Versio		1.7	Issue date: 11.10.		Page 1 / 8	
SECTION 1. Identification of the substance/mixtu			a aubatanaa/mixt	ure and of the com	nonv/undortoking	
SECTION 1: Identification of the substance/mixture and of the company/undertaking						
1.1.	product i					
		. (manufacturer/sup ion of the substance	. ,	90-720 Polyesterharz styrolarm		
1.2.	Relevant	identified uses of	the substance or mi	xture and uses advis	ed against	
		identified uses: putty for repair of	damaged surfaces or	uneven surfaces		
1.3.	Details of	the supplier of th	e safety data sheet			
	manufact FEYCOLC Maxhuette 93055 Reg	DR GmbH enstraße 6		Telephone: 0049 (0 Telefax: 0049 (0)94 E-mail info@feycolo Website: www.feyco	1/60 49 7-30 pr.com	
	Departme	ponsible for inforn nt for dangerous go mpetent person)		0049 (0)941/60 49 7 sd@feycolor.com	7-0	
1.4.	Emergenc	cy telephone numl sy telephone numbe ische Vergiftungsin		+49 (0) 700 24 11 2 +43 (0) 1406 43 43	1 12 (FCM)	
SEC	TION 2: H	azards identifica	tion			
2.1.	Classifica	ation of the substa	nce or mixture			
	Classifica	ation according to	Regulation (EC) No	1272/2008 [CLP]		
	The mixtu	re is classified as h	azardous according to	o regulation (EC) No 12	272/2008 [CLP].	
	Flam. Liq. Skin Irrit. 2 Eye Irrit. 2 Repr. 2 / H STOT RE	2 / H315 2 / H319 1361		ge/eye irritation	Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Suspected of damaging the unborn child. May cause damage to organs through	
<u>.</u>		mente	exposure)		prolonged or repeated exposure.	
2.2.	Label elei		ulation (EC) No. 127			
		ctograms				
			Warni	ing		
	Hazard st	atements				
	H226		able liquid and vapou	ır.		
	H315 H319		s skin irritation. s serious eve irritatior			

EEVCOLOD.

- H319 Causes serious eye irritation.
- H361 Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

i recautionary stater	nento
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P241	Use explosion-proof electrical equipment.
P280	Wear protective gloves and eye/face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
	easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Keep locked up.



Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

- 4.3. Indication of any immediate medical attention and special treatment needed
 - No special measures are necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:



alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons: strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

Vinyl toluene



999998 EN Page 4 / 8 **FEYCOLOR**[®]

EC No. 246-562-2 / CAS No. 25013-15-4

MEL/OES, TWA: 491 mg/m3; 100 ppm MEL/OES, STEL: 736 mg/m3; 150 ppm

Styrene

INDEX No. 601-026-00-0 / EC No. 202-851-5 / CAS No. 100-42-5

WEL, TWA: 430 mg/m3; 100 ppm WEL, STEL: 1080 mg/m3; 250 ppm

Additional information

TWA : long-term occupational exposure limit value STEL : short-term occupational exposure limit value Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0,7 mm; Breakthrough time (maximum wearing time) 60 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance: Physical state: Colour:	solid refer to label
Odour:	characteristic
Odour threshold:	not applicable
pH at20 °C:	n.a.
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	not applicable
Flash point:	33 °C
Evaporation rate:	not applicable
Flammability (solid, gas): Burning time (s):	not applicable
Upper/lower flammability or explosive limits:	
Lower explosion limit:	not applicable
Upper explosion limit:	not applicable
Vapour pressure at20 °C:	n.a.



ا ۔ : اس	No	00 700	Dolucetoria			FEYCOLOR®
Article Print d Versio	late:	90-720 21.11.2018 1.7	Polyesterharz Revision date: 2 Issue date: 11.2		999998 EN Page 5 / 8	
	Vapour d	ensity:		not applicable		
	Relative of Density a	at20 °C:		1,10 g/cm³		
	Solubility Water so	(ies): Iubility (g/L) at20 °(C.	insoluble		
		coefficient: n-octar		see section 12		
		tion temperature:		not applicable		
	-	sition temperature	:	not applicable		
	Viscosity	-		900 mPa·s		
	Explosive	properties:		not applicable		
	-	properties:		not applicable		
9.2.	Other info					
	Solid con	tent (%):		100 Wt %		
	solvent c Organic Water:	ontent: solvents:		0,00 Wt % 0,00 Wt %		
		eparation test (%):		< 3 Wt % (ADR/	RID)	
SEC		Stability and read	tivity		,	
	Reactivity	-				
10.1.	-	r ation available.				
10.2.	 Chemical stability Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. 					
10.3.	. Possibility of hazardous reactions Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.					
10.4.	Conditions to avoid Hazardous decomposition byproducts may form with exposure to high temperatures.					
10.5.	Incompatible materials No information available.					
10.6.	Hazardous decomposition products Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide smoke, nitrogen oxides.					
SEC	TION 11:	Toxicological info	ormation			
		tion according to Re n preparation itself a		1272/2008 [CLP]		
11.1.	Informati	on on toxicologica	l effects			
	Acute toxicity, calculated:					
	ATEmix calculated, inhalative (dust and mist): > 5 ppmV					
	Acute toxicity					
	Based on available data, the classification criteria are not met.					
	skin corrosion/irritation; Serious eye damage/eye irritation					
	Based on available data, the classification criteria are not met.					
	Respiratory or skin sensitisation					
	Based on available data, the classification criteria are not met.					
	CMR effe	cts (carcinogenicit	y, mutagenicity a	nd toxicity for re	production)	
		ctive toxicity				

Suspected of damaging the unborn child.

Specific target organ toxicity

Article No.:	90-720	Polyesterharz
Print date:	21.11.2018	Revision date: 24.10.2018
Version:	1.7	Issue date: 11.10.2018

999998 EN Page 6 / 8 **FEYCOLOR®**

Styrene

Specific target organ toxicity (repeated exposure): Causes damage to organs through prolonged or repeated exposure.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

Long-term Ecotoxicity

Toxicological data are not available.

- 12.2. **Persistence and degradability** No information available.
- 12.3. Bioaccumulative potential

No information available.

Bioconcentration factor (BCF)

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

160305 organic wastes containing hazardous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

Article Print d Versio	ate:	90-720 21.11.2018 1.7	Polyesterharz Revision date: 2 Issue date: 11.2		999998 EN Page 7 / 8		
14.2.	Land trans Sea transp	r shipping name port (ADR/RID): ort (IMDG): ort (ICAO-TI / IATA-	DGR):	POLYESTER RE	liquid base material SIN KIT liquid base material liquid base material		
14.3.	Transport	hazard class(es)		2			
14.4.	Packing g	roup		3			
14.5.	Environm	ental hazards					
	Land trans	port (ADR/RID)		not applicable			
	Marine pol	lutant		not applicable			
14.6.	Special pr	ecautions for use	r				
	Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8						
	Further information						
	Land trans	sport (ADR/RID)					
		riction code		E			
	Sea trans	port (IMDG)					
	EmS-No.			F-E, S-E			
	Air transp	ort (ICAO-TI / IATA	A-DGR)				
14.7.	Transport not applica	-	to Annex II of Ma	arpol and the IBC (Code		
SEC	ΓΙΟΝ 15: F	Regulatory inform	mation				
15.1.	Safety, he	alth and environm	ental regulations	/legislation specif	c for the substance or mixture		
	EU legisla		C C	•			
	Directive 2010/75/EU on industrial emissions VOC-value (in g/L): 0						
	National regulations						
	Restrictions of occupation Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).						
	Other reg	ulations, restrictio	ns and prohibitio	n regulations			
15.2.	Chemical Safety Assessment For the following substances of this preparation a chemical safety assessment has been carried out:						
	EC No. CAS No.	Chemi	cal name		REACH No.		
	246-562-2 25013-15-		luene		01-2119622074-50		
	202-851-5 100-42-5		9		01-2119457861-32		

SECTION 16: Other information

Full text of classification in section 3:

Acute Tox. 4 / H332	Acute toxicity (inhalative)
Skin Irrit. 2 / H315	skin corrosion/irritation
Eye Irrit. 2 / H319	Serious eye damage/eye irritation
Asp. Tox. 1 / H304	Aspiration hazard
Flam. Liq. 3 / H226	Flammable liquids
Repr. 2 / H361	Reproductive toxicity
STOT SE 3 / H335	Specific target organ toxicity (single
	exposure)

Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Flammable liquid and vapour. Suspected of damaging the unborn child. May cause respiratory irritation.

EEVCOLOD.



Article No.: Print date: Version:	90-720 21.11.2018 1.7	Polyesterharz Revision date: 24.10.2018 Issue date: 11.10.2018	999998 EN Page 8 / 8				
STOT	RE 1 / H372	Specific target organ toxicity (repeated exposure)	Causes damage to organs through prolonged or repeated exposure.				
Aquatio	c Chronic 3 / H41	2 Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.				
Abbre	viations and acr	onyms					
ADR	A	greement concerning the International Carriag	al des marchandises dangereuses par route (European e of Dangerous Goods by Road)				
AGW (· · ·	ccupational Exposure Limit Value					
CAS CLP		Chemicals Abstract Service					
CLP CMR		lassification, Labelling and Packaging arcinogenic, Mutagenic and Reprotoxic					
DNEL		erived No-Effect Level					
IATA-E	=	nternational Air Transport Association – Dangerous Goods Regulations					
ICAO-	TI I		ical Instructions for the Safe Transport of Dangerous				
IMDG		ternational Maritime Code for Dangerous Goo	ds				
PBT		ersistent, bioaccumulative, toxic					
PNEC	F	redicted No Effect Concentration					
REACI	H F	egistration, Evaluation, Authorisation and Rest	triction of Chemicals				
RID	F	èglement concernant le transport interna	ational ferroviaire de marchandises Dangereuses				
	(Regulations concerning the International Carria	ige of Dangerous Goods by Rail)				
UN	-	nited Nations					
LC		ethal Concentration					
LD	=	Lethal Dose					
VOC		Volatile Organic Compounds					
vPvB	٧	<i>r</i> persistent and very bioaccumulative					
E the e							

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.